

FLOWTREND REPLACEMENT SPECIALTY VALVES

FLOWTREND


SMARTER, FASTER FLUID HANDLING SOLUTIONS



Flowtrend W30-R Sample Valve

STANDARD FEATURES

- Typically used to extract product samples from process lines or tanks
- Connection type: Clamp
- Connections sizes: ½", ¾", 1", 1.5", 2"
- Large knurled nylon handle with non-galling alloy metal liner
- 316 stainless steel, 32Ra surface finish
- SIP - Steam or water flush connection ⅛" stainless steel tube available
- Quick disassembly for inspection and cleaning
- FPM/FKM seal with special pressure reducing orifice prior to seal
- FPM/FKM o-ring and body gasket
- Stem travel limited for increased safety
- Machined from bar stock



Flowtrend Air Blow Check Valve

STANDARD FEATURES

- Typically used to inject air into process lines to purge of product or rinse water
- Connection type: Clamp
- Connection sizes: 1", 1.5", 2", 2.5", 3", 4", 4.5"
- Air connection type: Air quick connect coupling
- 316 stainless steel, 32Ra surface finish
- Spring-loaded plug design: air-to-open, spring-to-close design prevents back flow
- Quick disassembly for inspection and cleaning
- FPM/FKM plug
- Filters for filtering air impurities



Flowtrend 660-R Sample Valve

STANDARD FEATURES

- Typically used to extract product samples from process lines or tanks
- Large knurled nylon handle, bronze available for higher pressure and/or higher temperature
- 316 stainless steel, 32Ra surface finish
- Connection type: Clamp
- Connections size: ½", ¾"
- Product discharge - ¼" hose barb or ½" clamp
- PTFE plug with o-ring
- Optional electro-polished ID
- Accessories Available
- Pressure: up to 100 psi [7 bar] service rating

Flowtrend® manufactured replacement valves for Alfa Laval® and Waukesha Cherry-Burrell® specialty valves. Flowtrend is not affiliated with, sponsored by, or endorsed by Alfa Laval or Waukesha Cherry-Burrell. Flowtrend's parts or products are not Alfa Laval® parts or products and Alfa Laval does not endorse, approve or warrant parts or products for their use.

11512 Space Center Blvd, Houston Texas 77059

P +1 281 990 8582 F +1 281 990 8644

WWW.FLOWTREND.COM

FLOWTREND REPLACEMENT SPECIALTY VALVES

Flowtrend LKC-2-R Check Valve

STANDARD FEATURES

- Typically used for preventing backflow of product in process lines
- Connection Type: Clamp or butt-weld
- Connection sizes: 1", 1.5", 2", 2.5", 3", 4"
- 304 or 316 stainless steel, 32Ra surface finish
- Quick disassembly for inspection and cleaning
- Nitrile seal ring



Flowtrend GC60-R Air Relief Valve

STANDARD FEATURES

- Typically used to eliminate air entrapment in process or CIP lines to prevent "air locking" of pumps
- 304 or 316 stainless steel, 32Ra surface finish
- Connection type: Clamp
- Connection sizes 1", 1.5", 2"
- Ball check seal design



Flowtrend A30S-R Sampling Valve

STANDARD FEATURES

- Typically used for tank sampling
- Operated by depressing spring-loaded stem
- Connection type: Clamp or bevel seat
- Connection sizes: 1.5", 2"
- 316 stainless steel, 32Ra surface finish
- Buna® or PTFE plug



Flowtrend® manufactured replacement valves for Alfa Laval® and Waukesha Cherry-Burrell® specialty valves. Flowtrend is not affiliated with, sponsored by, or endorsed by Alfa Laval or Waukesha Cherry-Burrell. Flowtrend's parts or products are not Alfa Laval® parts or products and Alfa Laval does not endorse, approve or warrant parts or products for their use.

11512 Space Center Blvd, Houston Texas 77059

P +1 281 990 8582 F +1 281 990 8644

WWW.FLOWTREND.COM